


## Cat 6A - Shielded 24 Port Patch Panel

### FEATURES

- Support Cat6A 500MHz requirement
- Backward compatibility for cat6 and Cat5E
- Hand screw, easy to open cover
- Unique design of balance circuit board and line pair decrease cross talk and increase allowance.
- Sturdy and easy-install design reduces installation and operating costs.
- Unique design of IDC terminating block allows 110 or krone tools.
- Compatible with 19-inch rack and cabinets.
- Labels for all ports ensure convenient operation.
- ID stripes for identifying port allocations

### TECHNICAL DETAILS

Dielectric strength: 1,000V RMS 60Hz/1min  
 Rated current: Maximum 1.5A  
 Insulation resistance(minimum): 500megohm  
 Contact resistance(maximum): 100milliohm  
 IDC clip: Phosphor Bronze Stamp Pin 0.35mm  
 Durability: 1500 times plugging, 250 times terminating  
 Module style RJ45 jack socket  
 Panel Frame: Cold-rolled steel sheet  
 electrostatic spray in black  
 19" Width, 1U Height



### COMPLIANCES

ISO/IEC 11801: 2002      EIA/TIA 568A/B Wiring standard      EEN50173-1: 2002  
 ANSI/EIA/TIA 568B.2: 2002      RoHS

### TRANSMISSION PERFORMANCE

Frequency (MHz)	1.0	4.0	8.0	10.0	16.0	20.0	25.0	31.3	62.5	100.0	200.0	250.0	300.0	400.0	500.0
Insertion loss (Db)	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.3	0.3	0.4	0.4	0.5
Next (Db)	75.0	75.0	75.0	74.0	69.9	68.0	66.0	64.1	58.1	54.0	48.0	46.0	42.9	37.9	34.0
PSNext (Db)	70.5	70.5	70.5	70.5	70.5	70.5	70.5	70.5	70.5	70.5	64.5	62.5	61.0	58.5	56.5
RL (Db)	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	28.0	22.0	20.0	18.5	16.0	14.0

### Ordering Information

003-SFTP-06A-024-00L